



CHARGE M3 —/T2C S



Info

- For charging stations

CHARGE M3 —/T1C S



Info

- For charging stations

Benefits

CHARGE M3 —/T2C S

- Resistant to microbes
- Resistant to oil, dust and water
- Special cable design for a long service life
- Flexible at low temperatures
- Withstands high mechanical stress, in particular abrasion and sliding demands

CHARGE M3 —/T1C S

- New two-chamber system for environmental protection of moving parts to the connection part
- Resistant to oil, dust and water
- Special cable design for a long service life
- Flexible at low temperatures
- Withstands high mechanical stress, in particular abrasion and sliding demands

Product Make-up

CHARGE M3 —/T2C S

- Cable for 1-phase charging up to 20A: ÖLFLEX® Charge 3G2.5 mm²+1x0.5 mm²
- Cable for 3-phase charging up to 20A: ÖLFLEX® Charge 5G2.5mm²+1x0.5mm²
- Cable for 1-phase charging up to 32A: ÖLFLEX® Charge 3G6mm²+1x0,5mm²
- Cable for 3-phase charging up to 32 A: ÖLFLEX® Charge 5G6mm²+1x0.5mm²
- Type 2 connectors are injection moulded in two-components process for optimal ergonomics

CHARGE M3 —/T1C S

- Cable for 1-phase charging up to 20A: ÖLFLEX® Charge 3G2.5 mm²+1x0.5 mm²
- Cable for 1-phase charging up to 32A: ÖLFLEX® Charge 3G6mm²+1x0,5mm²

Technical data

ETIM 5.0 Class-ID: EC002839
ETIM 5.0 Class-Description: Accessories for battery/charger

Certifications
according to VDE-AR-E2283-5
according to EN 61851-1

Temperature range
Flexing: -30°C to +50°C

Application range

- For installation in charging stations

| Article number | Version | Effective length (mm) | Copper index kg/1.000 pieces | Weight (kg/ 1000 pieces) | PU |
|--|-----------------------|-----------------------|------------------------------|--------------------------|----|
| Cut off clean, charging cable, vehicle connector type 2 (Total length: effective length +1m straight) | | | | | |
| 74880134 | Charging: 1 phase 20A | 5000 | 473 | 1280 | 1 |
| 74880135 | Charging: 1 phase 20A | 7000 | 627 | 1600 | 1 |
| 74880137 | Charging: 3 phase 20A | 5000 | 770 | 1840 | 1 |
| 74880138 | Charging: 3 phase 20A | 7000 | 1020 | 2360 | 1 |
| 74880141 | Charging: 1 phase 32A | 5000 | 1096 | 2160 | 1 |
| 74880142 | Charging: 1 phase 32A | 7000 | 1452 | 2800 | 1 |
| 74880145 | Charging: 3 phase 32A | 5000 | 1717 | 2900 | 1 |
| 74880146 | Charging: 3 phase 32A | 7000 | 2303 | 3820 | 1 |
| Cut off clean, charging cable, vehicle connector type 1 (Total length: effective length +1m straight) | | | | | |
| 74880127 | Charging: 1 phase 20A | 5000 | 479 | 1240 | 1 |
| 74880128 | Charging: 1 phase 20A | 7000 | 633 | 1540 | 1 |
| 74880130 | Charging: 1 phase 32A | 5000 | 1057 | 2100 | 1 |
| 74880131 | Charging: 1 phase 32A | 7000 | 1413 | 2740 | 1 |

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.
Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.
Photographs are not to scale and do not represent detailed images of the respective products.
Further colour combinations and lengths on request