



i Info

- For electric vehicles with type 1 vehicle inlet



CHARGE M3 T2P/T1C S

i Info

- For electric vehicles with type 1 vehicle inlet



CHARGE M3 T2P/T1C C

i Info

- For electric vehicles with type 1 vehicle inlet



CHARGE M3 T2P/T1C H

Benefits

- New two-chamber system for environmental protection of moving parts to the connection part
- Resistant to oil, dust and water
- Special cable design for a long service life
- Flexible at low temperatures
- Withstands high mechanical stress, in particular abrasion and sliding demands

Product Make-up

- Cable for 1-phase charging up to 20A: ÖLFLEX® Charge 3G2.5 mm²+1x0.5 mm²
- Cable for 1-phase charging up to 32A: ÖLFLEX® Charge 3G6mm²+1x0,5mm²
- Type 2 connectors are injection moulded in two-components process for optimal ergonomics

Technical data

ETIM 5.0 Class-ID: EC002839
 ETIM 5.0 Class-Description: Accessories for battery/charger

Certifications
 according to VDE-AR-E2283-5
 according to EN 61851-1

Temperature range
 Flexing: -30°C to +50°C

Application range

- For charging stations, electric and Plug-in Hybrid vehicles

Article number	Version	Effective length (mm)	Copper index kg/1.000 pieces	Weight (kg/1000 pieces)	PU
Plug type 2, charging cable, vehicle connector type 1					
74880152	Charging: 1 phase 20A	5000	409	2740	1
74880147	Charging: 1 phase 20A	7000	571	2000	1
74880149	Charging: 1 phase 32A	5000	961	2560	1
74880093	Charging: 1 phase 32A	7000	1317	3200	1
Plug type 2, charging cable spiralsised, vehicle connector type 1					
74880148	Charging: 1 phase 20A	5000	1006	2880	1
74880151	Charging: 1 phase 32A	5000	2474	5280	1
Plug type 2, charging cable Helix, vehicle connector type 1					
74880270	Charging: 1 phase 32A	5000	1059	1680	1

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request. Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges. Photographs are not to scale and do not represent detailed images of the respective products. Further colour combinations and lengths on request